

# **TECHNICAL DATA SHEET**

## PRODUCT

Date: 06/03/15

### PROCOL TOP 120

Page 1 to 1 Version 3

#### **1. PRODUCT DESCRIPTION**

PROCOL TOP 120 is a double cure emulsion of medium viscosity. Solids content: 40% (purple colour).

Shelf life: 2 years at 20°C in a dark room (diazo's shelf life: 1 year). Sensitized: 3 months at 20°C in a dark room.

#### 2. PRINTING APPLICATION

Resisting to solvent based inks and water based inks.

#### 3. SENSITIZING

Prepare the sensitizer by half filling the bottle with water. Dissolve the powder by shaking the bottle for at least one minute. Mix the sensitizer into the emulsion with a non-metallic instrument. Leave the sensitized emulsion to stand at least one hour to eliminate air bubbles.

#### EXPOSURE TIME:

A preliminary test can be done using the following guidelines:

Use of a 3000 W lamp at 90 cm

Mesh:	Time (seconds):	Mesh:	Time (seconds):
120 T White (1coat)	40	140 T Gold (1 coat)	75
120 T White (2 coats)	60	165 T Gold (2 coats)	100

#### 4. FIRST AID PROCEDURES

INHALATION:	None.
EYE CONTACT:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
	In the event of persistent irritation or any lesions, consult an oculist.
SKIN CONTACT:	Wash off with soap and water.
INGESTION:	Clean mouth with water. Do not induce vomiting.

### 5. SUPPLIED IN

0.9 Kg



4.5 KG

