

PRODECRAN
345 RUE DE L'INDUSTRIE
Z.I. DU VERMEILLET
30380 SAINT-CHRISTOL LES ALES
France (EEC)

Tel.: (+33) 4 66 60 90 50 Fax: (+33) 4 66 60 94 09

TECHNICAL DATA SHEET

PRODUCT
Date: 06/03/15

Page 1 to 1
Version 3

1. PRODUCT DESCRIPTION

PROCOL TOP is a photopolymer emulsion (double cure emulsion) of high viscosity. Solids content: 41% (purple colour).

Shelf life: 2 years at 20°C in a dark room (diazo's shelf life: 1 year). Sensitized: 3 months at 20°C in a dark room.

2. PRINTING APPLICATION

Resisting to all kinds of inks (water based inks, uv inks, uv water inks, solvents). Very good definition. Fast exposure time.

3. SENSITIZING

Prepare the sensitizer by half filling the bottle with water. Dissolve the powder by shaking the bottle for at least one minute. Mix the sensitizer into the emulsion with a non-metallic instrument. Leave the sensitized emulsion to stand at least one hour to eliminate air bubbles.

EXPOSURE TIME:

A preliminary test can be done using the following guidelines:

Use of a 3000 W lamp at 90 cm: 1 coat

Mesh:	Time (seconds):	Mesh:	Time (seconds):
120 T White	45	120 T Gold (2 coats)	120
120 T Gold	75	165 T Gold	60

4. FIRST AID PROCEDURES

INHALATION: None

EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

In the event of persistent irritation or any lesions, consult an oculist.

SKIN CONTACT: Wash off with soap and water.

INGESTION: Clean mouth with water. Do not induce vomiting.

5. SUPPLIED IN

 $0.9\,\mathrm{Kg}$ 4.5 Kg





TDS PROCOL TOP www.prodecran.com