

PRODECRAN
345 RUE DE L'INDUSTRIE
Z.I. DU VERMEILLET
30380 SAINT-CHRISTOL LES ALES
France (EEC)

Tel.: (+33) 4 66 60 90 50 Fax: (+33) 4 66 60 94 09

TECHNICAL DATA SHEET

PRODUCT
Date: 06/03/15

PROCOL ZX+

Page 1 to 1
Version 2

1. PRODUCT DESCRIPTION

PROCOL ZX+ is a diazo emulsion resisting to all kinds of inks. Medium viscosity, colour blue. Solids content: 35%.

Shelf life: 2 years at 20°C in a dark room (diazo's shelf life: 1 year). Sensitized: 3 months at 20°C in a dark room.

2. PRINTING APPLICATION

Resisting to all kinds of inks (water based inks, uv inks, uv water inks, solvents) including aggressive pastes. Very fast, it is recommended for a very poor UV light source. Suitable for any work requiring a very good mechanical resistance.

3. SENSITIZING

Prepare the sensitizer by half filling the bottle with water. Dissolve the powder by shaking the bottle for at least one minute. Mix the sensitizer into the emulsion with a non-metallic instrument. Leave the sensitized emulsion to stand at least one hour to eliminate air bubbles.

EXPOSURE TIME:

A preliminary test can be done using the following guidelines:

Use of a 3000 W lamp at 90 cm, 1 coat + 1 coat

Mesh:	Time (seconds):	Mesh:	Time (seconds):
54 T White	132	120 T white	108
90 T White	120	140 T white	90

4. FIRST AID PROCEDURES

INHALATION: None

EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

In the event of persistent irritation or any lesions, consult an oculist.

SKIN CONTACT: Wash off with soap and water.

INGESTION: Clean mouth with water. Do not induce vomiting.

5. SUPPLIED IN

 $0.9\,\mathrm{Kg}$ 4.5 Kg





TDS PROCOL ZX+ www.prodecran.com